

BEARINGS RADIAL CLEARANCE

关节轴承径向游隙

Bearing No. 型号	Bearing Component 组成	Bearing Bore 孔径	C2	Normal 基本	C3
		mm	um	um	um
GIR..DO	Steel on Steel	~12		15~50	
GIR..DO 2RS		15~20		20~65	
GAR..DO		25~35		30~85	
GAR..DO 2RS		40~60		35~100	
		70~80		45~120	
GI..	Steel on Brass	~10		5~35	
GA..		12~20		10~40	
SI..		22~40		10~50	
SA..					
GIR..UK	Steel on PTFE	~12		0~30	
GIR..UK 2RS		15~20		0~40	
GAR..UK		25~35		0~50	
GAR..UK 2RS		40~60		0~55	
GIR..NIRO		70~80		0~60	
GAR..NIRO					
SI..D	Steel on PTFE	~10		5~30	
SA..D		12~18		5~35	
SI..SS		20~25		5~45	
SA..SS		30~40		5~55	
SI..BD	Steel on PTFE	4~10		5~40	
SA..BD		12~20		5~50	
GE..E	Steel on Steel	~12	8~32	32~68	68~104
GE..ES		12~20	10~40	40~82	82~124
GE..ES 2RS		20~35	12~50	50~100	100~150
GE..FO		35~60	15~60	60~120	120~180
GE..FO		60~90	18~72	72~142	142~212
GE..FO 2RS		90~140	18~85	85~165	165~245
GE..LO					
GE..HO 2RS					
GE..PB					
GE..DB					
GL..PB					
GE..UK	Steel on PTFE	~12	0~25	0~32	15~45
GE..UK 2RS		15~20	0~30	0~40	20~60
GE..SS		25~35	0~35	0~50	25~65
		40~60	0~40	0~60	30~80
		70~90	0~50	0~72	35~90
		100~140	0~60	0~85	40~100
GE..FW	Steel on PTFE	~10	5~40	10~60	40~90
GE..FW 2RS		10~18	6~50	15~75	65~105
G..PW		18~30	7~60	20~90	75~120
G..DB		30~50	9~70	25~110	95~150
G..SS		50~80	10~80	30~130	115~175
GL..PW		80~120	12~90	35~150	135~200