

Outer rings:


Bearing steel, hardened, ground, polished,
axial plain washers on both sides

Inner rings:

Bearing steel, hardened, ground, polished,
full complement needle roller set

外圈：轴承钢，淬火，磨加工，抛光，两侧轴向滑动垫圈

内圈：轴承钢，淬火，磨加工，抛光，满滚针配置



Bearing No. 型号	Dimensions in millimeters 尺寸 mm						Properties 性能				Weight 重量	
	d	D	B	C	d2	r	Crw	Corw	Curw	NDG		
						min	KN	KN	KN	1/min		≈kg
NATV 5 PP	5	16	12	11	12.5	0.15	4.9	6.5	0.86	3800		0.015
NATV 6 PP	6	19	12	11	15	0.15	5.4	7.9	1.04	3100		0.021
NATV 8 PP	8	24	15	14	19	0.3	7.8	11.4	1.43	2500		0.041
NATV 10 PP	10	30	15	14	23	0.6	9.5	14.6	1.84	2100		0.064
NATV 12 PP	12	32	15	14	25	0.6	9.7	15.4	1.95	1800		0.069
NATV 15 PP	15	35	19	18	27.6	0.6	12.8	23	2.9	1600		0.101
NATV 17 PP	17	40	21	20	31.5	1	14.8	26.5	3.05	1400		0.147
NATV 20 PP	20	47	25	24	36.5	1	20.6	42	5.2	1300		0.245
NATV 25 PP	25	52	25	24	41.5	1	20.5	44	5.4	1000		0.281
NATV 30 PP	30	62	29	28	51	1	30.5	62	7.8	850		0.468
NATV 35 PP	35	72	29	28	58	1.1	33	71	8.9	750		0.63
NATV 40 PP	40	80	32	30	66	1.1	41	88	11	650		0.832
NATV 50 PP	50	90	32	30	76	1.1	40	92	11.6	550		0.969

Crw: Effective dynamic load rating as track roller (radial)

Corw: Effective static load rating as track roller (radial)

Curw: Fatigue limit load

NDG: Speed (for continuous operation and grease lubrication)