


YOKE TYPE CAM FOLLOWER - NATV..

SYLB®

Outer rings:
Bearing steel, hardened, ground, polished,
gap seals on both sides

Inner rings:
Bearing steel, hardened, ground, polished,
full complement needle roller set

外圈：轴承钢，淬火，磨加工，抛光，两侧间隙密封
内圈：轴承钢，淬火，磨加工，抛光，满滚针配置



Bearing No.		Dimensions in millimeters						Properties				Weight	
型号		尺寸 mm						性能				重量	
	d	D	B	C	d2	r	Crw	Corw	Curw	NDG			
						min	KN	KN	KN	1/min		≈kg	
NATR 5	5	16	12	11	12.5	0.15	4.9	6.5	0.86	3800		0.015	
NATR 6	6	19	12	11	15	0.15	5.4	7.9	1.04	3100		0.021	
NATR 8	8	24	15	14	19	0.3	7.8	11.4	1.43	2500		0.042	
NATR 10	10	30	15	14	23	0.6	9.5	14.6	1.84	2100		0.065	
NATR 12	12	32	15	14	25	0.6	9.7	15.4	1.95	1800		0.072	
NATR 15	15	35	19	18	27.6	0.6	12.8	23	2.9	1600		0.109	
NATR 17	17	40	21	20	31.5	1	14.8	26.5	3.05	1400		0.152	
NATR 20	20	47	25	24	36.5	1	20.6	42	5.2	1300		0.254	
NATR 25	25	52	25	24	41.5	1	20.5	44	5.4	1000		0.285	
NATR 30	30	62	29	28	51	1	30.5	62	7.8	850		0.481	

Crw: Effective dynamic load rating as track roller (radial)
Corw: Effective static load rating as track roller (radial)
Curw: Fatigue limit load
NDG: Speed (for continuous operation and grease lubrication)